

# TWN4 MULTITECH 2 BLE

*TWN4 MULTITECH 2*

RFID READER/WRITER FOR LF, HF, NFC, BLE



TWN4 MultiTech 2 BLE

ELATEC's TWN4 family of RFID readers and writers allows users to read and write to almost any 125 kHz and 13.56 MHz tags and/or labels. It supports all major transponders from various suppliers like ATMEL, EM, ST, NXP, TI, HID etc. and ISO standards like ISO 14443A/B (T-CL), ISO 15693, ISO 18092 / ECMA-340 (NFC).

The TWN4 MultiTech 2 BLE reader has integrated RFID (LF & HF) and Bluetooth Low Energy (BLE), which is supported by mobile phones with Android version 4.3 or greater, iOS 8.0 or greater and PCs with Windows (new Bluetooth hardware integrated). The app on the reader communicates with the BLE module with easy commands and has direct enhancement to the GATT structure, which gives you the flexibility to write your custom apps.

Special features:

- + Powerful SDK for writing apps which are executed directly on the reader
- + Firmware update in the field possible
- + On-board 18 kB flash storage, e.g. for storing user accessible non-volatile data
- + Direct chip-commands support
- + Two on-board SAM sockets (Secure Access Module)
- + CCID and PC/SC 2.01
- + 4 GPIOs
- + Supports Apple VAS and ECP 2.0<sup>8)</sup>
- + Bluetooth V4.1, upgradeable to V4.2, API, flexible GATT structure up to 8 connections simultaneous, AES128 supported
- + Supports quick (re)configuration over network and over wireless interface with TWN4 CONFIG Card
- + TWN4 Upgrade Card for P and PI options available on request
- + 3D construction data (STEP) available on request



Elevator



EV Chargers



Access



Shop POS



Fitness Equipment



Ticket POS



PC Log-on



Document Management



Driver ID



Vending



Parking



Gaming



Locker Locks



Time Attendance



Industrial PC

**TECHNICAL DATA**

FREQUENCY	125 kHz (LF) / 13,56 MHz (HF) / 2.4 GHz (BLE)
ANTENNA(S)	Integrated
HOUSING	Material: ABS UL94-V0
DIMENSIONS (L X W X H)	88 mm x 56 mm x 18 mm
POWER SUPPLY	4.3 V - 5.5 V via USB; via generic interface (X1) 3.3 V ± 5%; RS-232 requires 5 V external power supply Limited power source according to the safety norms listed in the respective declaration of conformity, short-circuit current < 8 A
CURRENT CONSUMPTION	RF field on: 120 mA typically + 16 mA (BT) / Sleep: 500 µA typ. / Cyclic Operation: TBD
TEMPERATURE RANGE	Operating: -25 °C up to +70 °C (-13 °F up to +158 °F) Storage: -45 °C up to +75 °C (-49 °F up to +167 °F)
RELATIVE HUMIDITY	5% to 95% non-condensing
READ- / WRITE DISTANCE	LF and HF: Up to 100 mm / 4 inch, depending on environment and transponder BT: up to several meters/feet (configurable, up to +8 dBm power)
OPERATING MODES (USB)	USB keyboard emulation – USB virtual COM port – CCID / PC/SC 2.01
BLUETOOTH LOW ENERGY	Bluetooth V4.1, software upgradable to V4.2; easy to integrate in reader App with commands, optional BGAPI protocol; Standards as GAP, SM, L2CAP, ATT; predefined GATT structure; up to 8 connections; AES128 support
MTBF	500,000 hours
WEIGHT	Approx. 118 g (with cable)
SUPPORTED TRANSPONDERS (STANDARD) 13.56 MHZ	<p><u>ISO14443A:</u> LEGIC Advant<sup>1</sup>, MIFARE Classic EV1<sup>2</sup>, MIFARE Classic, MIFARE Mini, MIFARE DESFire EV1, MIFARE DESFire EV2<sup>3</sup>, MIFARE DESFire Light<sup>4</sup>, MIFARE Plus S, X, MIFARE Pro X<sup>5</sup>, MIFARE Smart MX<sup>5</sup>, MIFARE Ultralight, MIFARE Ultralight C, MIFARE Ultralight EV1<sup>2</sup>, NTAG2xx, SLE44R35<sup>5</sup>, SLE66Rxx (my-d move)<sup>5</sup>, Topaz</p> <p><u>ISO18092 ECMA-340:</u> NFC Forum Tag 1-5, NFC Peer-to-Peer, Sony FeliCa<sup>6</sup>, NFC Active and passive communication mode</p> <p><u>ISO14443B:</u> Calypso<sup>5</sup>, Calypso Innovatron protocol<sup>5</sup>, CEPAS<sup>5</sup>, HID iCLASS<sup>1</sup>, Moneo<sup>5</sup>, Pico Pass<sup>7</sup>, SRI4K, SRIX4K, SRI512, SRT512</p> <p><u>ISO15693:</u> EM4x33<sup>5</sup>, EM4x35<sup>5</sup>, HID iCLASS<sup>1</sup>, HID iCLASS SE/SR<sup>1</sup>, ICODE SLI, LEGIC Advant<sup>1</sup>, M24LR16/64, MB89R118/119, SRF55Vxx (my-d vicinity)<sup>5</sup>, Tag-it, PicoPass<sup>7</sup></p> <p><u>Mobile support:</u> Apple VAS<sup>8</sup>, ECP 2.0<sup>8</sup></p>
SUPPORTED TRANSPONDERS (STANDARD) 125 KHZ9)	AWID, Cardax, CASI-RUSCO, Deister <sup>10</sup> , EM4100, 4102, 4200 <sup>11</sup> , EM4050, 4150, 4450, 4550, EM4305 <sup>12</sup> , FDX-B1 <sup>3</sup> , EM4105 <sup>13</sup> , UltraProx <sup>13</sup> , HITAG 1 <sup>14</sup> , HITAG 2 <sup>14</sup> , HITAG S <sup>14</sup> , ICT <sup>4</sup> , IDTECK, Isonas, Keri, Miro, Nedap <sup>10</sup> , PAC <sup>4</sup> , Pyramid, Q5, T5557, T5567, T5577, TIRIS/HDX <sup>13</sup> , TITAN (EM4050), UNIQUE, ZODIAC
SUPPORTED TRANSPONDERS (OPTION P)	All Standard Transponders, Cotag, G-Prox <sup>10</sup> , HID DuoProx II, HID ISO Prox II, HID Micro Prox, HID ProxKey III, HID Prox, HID Prox II, Indala, ioProx, Nexwatch
SUPPORTED TRANSPONDERS (OPTION PI)	Requires TWN4 SIO Card, All Standard Transponders, All Option P Transponders, HID iCLASS, HID iCLASS SE/SR/Elite, HID iCLASS SEOS (Facility Code/PAC) <sup>15</sup>
OS SUPPORT	Windows Embedded CE <sup>4</sup> , 7 (32-/64-bit), 8, 8.1, 10, Linux, Android <sup>4</sup> , iOS <sup>4</sup> , MAC OS X <sup>4</sup>
PERIPHERAL INTERFACES	USB, RS-232, TTL serial (logic level 3.3 V, CMOS, 5 V tolerant), I <sup>2</sup> C, 4 GPIOs, Clock/Data, Wiegand, Bluetooth Low Energy (BLE)
TRANSMISSION SPEED	Host: USB Full speed (12 Mbit/s), RS-232: up to 115,200 baud, HF Air: up to 848 kbit/s, BT Air: up to 100 kbit/s
CERTIFICATION NAME	TWN4 MultiTech 2
CERTIFICATION(S)	CE/RED, FCC, IC, REACH and RoHS-III compliant, Apple VAS and ECP 2.0 certified and many more

ORDER CODE(S)	9500450	USB Black Standard Option
	9500451	USB Option P Black
		USB Option PI Black

<sup>1</sup>UID only <sup>2</sup>r/w enhanced security features on request <sup>3</sup>EV2/EV3 supported as part of the EV1 downward compatibility <sup>4</sup>On request <sup>5</sup>r/w in direct chip command mode <sup>6</sup>UID + r/w public area <sup>7</sup>UID only, read/write on request <sup>8</sup>For Apple licensees only and eligible implementers. Please contact ELATEC for details. <sup>9</sup>125 kHz technology requires a Russian local test and import license from the ministry of Trade and Industry (MINPROMTORC). This license has to be in place before Elatec can accept any order to be shipped to Russia <sup>10</sup>Hash value only <sup>11</sup>Only emulation of 4100, 4102 <sup>12</sup>From FW V4.05 <sup>13</sup>134.2 kHz only <sup>14</sup>Without encryption <sup>15</sup>UID + PAC (Facility Code), r/w on request

## ACCESSORIES

HOLDER(S)	9000400	Snap-In Holder black	
CABLES	9400134	USB cable type A 45 cm / 17.72	
	9400142	USB cable mini 25 cm / 9.84 inch	

ELATEC reserves the right to change any information or data in this document without prior notice. ELATEC declines all responsibility for the use of this product with any other specification but the one mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification. Disclaimer: All names used in this document are registered trademarks of their respective owners.